



minipack® - torre
Packaging machines and systems

BUNDLING MACHINE MS 50 L

**SEMI-AUTOMATIC SLEEVE WRAPPER WITH LINE INFEED - INCORPORATED
TUNNEL - SEALING BAR 500 MM**

semiautomatic or automatic with motorised belt



DESCRIPTION

The new series of **Minipack-Torre** bundling machines is characterised by the great versatility of the models combining efficiency, reliability and high performance. This all guarantees ideal working conditions in any

minipack@torre S.p.A.

Sede legale - Via Provinciale, 54 - 24044 DALMINE (BG) Italy

P.IVA - C.F.: 01633550163 - Capitale sociale 619.200,00 i.v. - Reg. Imprese di Bergamo 01633550163 - REA n. 224151



situation the user carries out the activity.

The models of the MS L and AL range represent the best solution for incorporating the machine in production lines, as they are all set up for automatic management of the line infeed and outfeed exchange signals.

The MS L and AL Bundling Machines wrap both individual and multiple products in polyethylene film. They can wrap products as long as 1500 mm. Thanks to the control selector, the operator can choose whether to work in automatic or semiautomatic mode.

TECHNICAL FEATURES

Power supply	V	220/400
Phase	ph	3
Electric Power	kW	12
Electric consumption	kWh	10
Air Pressure	bar	6
Air Consumption per cycle	nl	6
Hourly production	p/h (pph)	Up to 9 ppm
Sealing Bar	mm	500
MAX product height	mm	250
MAX reel dimensions	mm	Ø 350x480
Worktop height	mm	Standard 850+25
Machine dimensions	mm	2500x1150x h.1400
Tunnel infeed dimensions	mm	400x h.270
Tunnel chamber length	mm	1100
Machine weight	kg	650



minipack® - torre
Packaging machines and systems

minipack®-torre shall not be held liable for typos or printing errors in this catalogue. It also reserves the right to make changes to the specified features without prior notice. All trademarks are property of their respective owners and are hereby acknowledged.

MAIN FEATURES

- Sealing bar with a film cutting blade (no smoke during the sealing step)
- Height of the worktop: 850 +/-25mm
- Air consumption: 8 NL/min. Air supply required 6 bar
- Power supply: Option between 3phases 220V and 400V 3phases + Neutral
- Photoelectric cell that blocks the sealing bar if it encounters an obstacle in its path
- Automatic wrapping system of the film reels with dragging rollers
- Heat-shrinking film reels with max diameter 350 mm - thickness between 35 and 100 microns
- Heat-shrinking tunnel insulated with rock wool and heated with resistors. Forced ventilation with air circulation
- The temperature of the sealing bar and the tunnel is controlled with PID temperature controllers
- Internal conveyor belt in the heat-shrinking Tunnel, driven by a gear motor with adjustable speed and featuring a steel grid, shaped like thin mesh with side chains
- Switch to change the cycle from automatic and manual to semi-automatic with a pedal

minipack®-torre S.p.A.

Sede legale - Via Provinciale, 54 - 24044 DALMINE (BG) Italy

P.IVA - C.F.: 01633550163 - Capitale sociale 619.200,00 i.v. - Reg. Imprese di Bergamo 01633550163 - REA n. 224151