



MVS52 DV X

DOUBLE TANK TROLLEY VACUUM - SEALING BARS 530 MM
VACUUM MACHINE WITH CARRIAGE



DESCRIPTION

Designed in cooperation with some important chefs, the **MVS X chamber vacuum sealers** line has a series of avant-garde capabilities and highly technological content, with the utmost ease of use. Thanks to the collaboration with industry professionals, this line of **vacuum packaging machines** is equipped with specific functionalities for the needs of professional packaging.

The series models are equipped with a tactile control keypad that avoids any risk of liquid infiltration in the board, thanks to its hermetic application on the front of the bodywork. In addition, with a few touches on the control panel you can access up to 10 customized programs.

A special message on the display notifies you whenever you need to change the oil. In addition, an internal electronic sensor can read the vacuum realized in the chamber. It is also possible to calibrate these **vacuum packaging machines** according to the level of atmospheric pressure at different altitudes.



TECHNICAL FEATURES

Electric power supply	V	208
Phase	ph	3
Dimensions of sealing bars	mm	530 (no. 2 side bars per tank - Tot.4)
Packaging cycle (Vacuum 99.9%)	sec.	Vacuum =22 - Air re-immission= 5
Vacuum pump	mc/h	40
Work surface height	mm	893
Machine dimensions with the lid open	mm	1278x784x h.1344
Machine dimensions with the lid closed	mm	1278x784x h.985
Machine weight (Net/Gross)	kg	268/300
Available chamber dimensions (Tank+lid)	mm	399x519x h.200 (2 tanks)

minipack@-torre shall not be held liable for typos or printing errors in this catalogue. It also reserves the right to make changes to the specified features without prior notice. All trademarks are property of their respective owners and are hereby acknowledged.

TECHNICAL DRAWING

